

Cordless pipe cutting machine **REMS CENTRO 22 V**

Mobile cutting and deburring up to Ø 115 mm. Super fast.

REMS

for Professionals

since
1909

REMS 22V 
LI-ION TECHNOLOGY



Patent EP 1 782 904
Super fast. Right angled.
Chip-free. No outer burr.
Dry cutting.

German Quality Product

REMS 22V 
LI-ION TECHNOLOGY



REMS Cento 22 V – Mobile cutting and deburring up to Ø 115 mm. Universal for many pipe types.

REMS Cento 22 V is a compact, mobile, cordless pipe cutting machine for fast, right-angled and chipless cutting of pipes, without outside burr. The machine can be used universally for cutting plastic, metal and composite tubes. The stable, torsion-free cast construction enables fast, right angled cutting. The REMS Li-Ion 22 V technology sets standards in terms of economy and user friendliness and enables the user to cut ultra fast, e.g. stainless steel pipes with Ø 54 mm in only 7 s. The battery technology and low weight including battery of just 17.6 kg enable easy, effortless working everywhere on site. For trade and industry. For the building site and the workshop.

- 1 Ideal for pressfitting systems**
Right angled cutting, according to requirements
Chip-free, no chips in piping system
No outer burr, no damage to O-ring by outer burr
Dry, no damage to the O-ring by coolants-lubricants.
Fast, prevents degradation of pipe material through overheating.
- 2** Compact, mobile cordless pipe cutting machine for fast, right angled, cutting with no outer burr. Handy and light, drive unit with battery only 17.6 kg. Stable, distortion-free cast construction for right angled cutting.
- 3** Easy pipe-cutting through specially designed cutter wheel.
- 4 Patent EP 1 782 904**
Powered cutter wheel and linear advance for fast cutting
- 5** Power saving feed-in through easy to grip, proven advance-lever and needle bearing mounted machine screw spindle.
- 6** Cutter wheel protected – as movement restricted to before any contact with the rollers.
- 7** Practical handle for easy transport.
- 8** Connection for driving outer/inner pipe deburrer REMS REG 10 – 54 E.
- 9** For workbench, stand or wheel stand.



- 10** An alternative feed lever is available for operating the drive unit on the floor, see accessories.
- 11** 4 strong hardened precision tubular steel running rollers on ball bearings for low-friction turning of the pipes \varnothing 22–115 mm, \varnothing $\frac{3}{4}$ –4" to be cut, trapezoidally arranged, replaceable. No setting work required in the whole working range \varnothing 22–115 mm. Stainless tubular steel rollers as accessory. Cutting of pipes \varnothing 8–22 mm by placing two pipe sections \varnothing 28 \times 220 mm on the running rollers.
- 12 Drive**
Robust gear, precisely mounted in roller and needle bearings, maintenance-free. Powerful 21.6 V battery motor, e.g. stainless steel pipe \varnothing 54 mm in just 7 s. Ideal speed 84 rpm for optimum cutting speed of the pipes.
- 13** Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check with charging level indication by a 2-coloured green/red LED.
- 14** Safety foot-switch with emergency stop.
- 15 Li-Ion 22 V Technology**
Highly resistant Li-Ion 21.6 V battery with 5.0 Ah or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 5.0 Ah battery for approx. 280 stainless steel pipe sections, 9.0 Ah for approx. 520 stainless steel pipe sections of the \varnothing 22 mm pressfitting systems with one battery charge.
- 16** Graduated charging status check by coloured LEDs.
- 17** Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power.
- 18** Rapid charger 100–240 V, 90 W. Rapid charger 100–240 V, 290 W, for shorter charging times, as accessory.
- 19** 220–240 V/21.6 V, 40 A output voltage supply for mains operation 230 V instead of Li-Ion battery 21.6 V, as accessory.
- 20 REMS cutter wheels**
Top German quality. Cutter wheels specially designed to the performance capability of the REMS Cento 22 V and for numerous pipe materials with variable cutting geometries for fast cutting with no outer burr. Specially hardened, from proven, through-hardened REMS die-steel, ensuring long service life.
- 21 REMS pipe deburrer**
Inner pipe deburrer REMS REG 28–108 for pipes \varnothing 28–108 mm, \varnothing $\frac{3}{4}$ –4", for electric drive with the REMS Cento and REMS Cento 22 V pipe cutting machine, as an accessory. Outer/inner pipe deburrer REMS REG 10–54 E for pipes \varnothing 10–54 mm, \varnothing $\frac{1}{2}$ –2 $\frac{1}{8}$ ", for electric drive with the REMS Cento pipe and REMS Cento 22 V pipe cutting machine, as an accessory.
- 22 Marking device**
Marking device for marking the insertion depth for fittings on pipes, as an accessory.





REMS Cento 22 V

REMS Cento 22 V Basic. Cordless pipe cutting machine for fast, right angled, cutting of pipes with no outer burr Ø 8–115 mm. For pipes of the press fitting systems made from stainless steel, carbon steel, copper, Ø 8–108 mm. For steel pipes EN 10255 (DIN 2440) DN 6–100, Ø ½–4", Ø 10–115 mm, cast pipes (SML) EN 877 (DIN 19522) DN 50–100, plastic tubes SDR 11, wall thickness $s \leq 10$ mm, Ø 10–110 mm, Ø ½–4", composite tubes Ø 10–110 mm. With maintenance-free gear, powerful 21.6 V battery motor. Speed 84 rpm. Machine status check with overload protection, temperature monitoring, battery charging status check. Rollers in hardened precision steel pipe for pipes Ø 22–115 mm, Ø ¾–4". Safety foot-switch. Li-Ion 21.6 V, 5.0 Ah battery, 100–240 V, 50–60 Hz, 90 W rapid charger. Ring spanner. Without cutter wheel. For workbench, stand or wheel stand. In a carton.

Art.-No. 845002 R220

Accessories



REMS REG 10–54 E. Outer/inner pipe deburrer.

Art.-No. 113835 R



REMS REG 28–108, inner pipe deburrer for pipes Ø 28–108 mm, Ø ¾–4", for electric rotary drive by the cutting wheel of the REMS Cento, REMS Cento 22 V pipe cutting machine (with REMS cutting wheel Art. No. 845050 or 845053).

Art.-No. 113840 R



Stand

Art.-No. 849315 R



Wheel stand

Art.-No. 849310 R



REMS Jumbo E

Art.-No. 120240 R



REMS Jumbo

Art.-No. 120200 R



REMS Herkules 3B, tripod

Art.-No. 120120 R



REMS Herkules Y, clamping fixture for work bench

Art.-No. 120130 R

Accessories



Battery Li-Ion 21.6 V, 5.0 Ah

Art.-No. 571581 R22

Battery Li-Ion 21.6 V, 9.0 Ah

Art.-No. 571583 R22

Rapid charger 100–240 V, 50–60 Hz, 90 W

Art.-No. 571585 R220

Rapid charger 100–240 V, 50–60 Hz, 290 W

Art.-No. 571587 R220

Voltage supply 220–240 V/21.6 V, 50–60 Hz, 40 A,
for mains operation instead of battery Li-Ion 21.6 V

Art.-No. 571578 R220

Feed lever with spring plug for operating the drive unit on the floor.

Art.-No. 845218 R

REMS cutter wheel Cu-INOX

for stainless steel pipes of pressfitting systems,
copper, carbon steel

Art.-No. 845050 R

REMS cutter wheel Cu

specially for pipes of copper pressfitting systems

Art.-No. 845053 R

REMS cutter wheel St

for steel pipes, cast iron pipes (SML)

Art.-No. 845052 R

REMS cutter wheel V for plastic and multilayer
composite pipes, wall thickness $s \leq 10$ mm

Art.-No. 845051 R

REMS cutter wheel C-SF especially for pipes of the
pressfitting systems and push fitting systems made
from carbon steel, simultaneously produces a chamfer.

Art.-No. 845055 R

Pipe support 1, height adjustable, for pipes
 $\varnothing 40-110$ mm, $\varnothing 1\frac{1}{2}-4$ ", with operation
of the drive unit with feed lever on the floor

Art.-No. 845220 R

Hardened, precision tubular steel rollers (pack of 4)

Art.-No. 845118 R

Stainless tubular steel INOX rollers (pack of 4)

Art.-No. 845110 RINOX

Marking device for marking the insertion depth
for fittings on pipes. For REMS Cento,
REMS Cento 22 V.

Art.-No. 845530 R

REMS Lumen 2800 22 V Set Power-Edition,
cordless LED flood lamp

Art.-No. 175210 R220G

Sale through specialist dealers.

REMS Ireland

Tel.: 01 8700 008

Email: IRL@rems.de

www.rems.de

Representative: Gerry Phipps

Mobile: 087 920 4068

Email: gerry.phipps@rems.de



www.rems.de



@remstools